

Python Specification Data

The following specification data are as per the manufacturer of this product and are for use as a general guideline only. VersaFrame Inc is solely a supplier/distributor of these products. The following data has not been tested by VersaFrame Inc. but rather supplied by the manufacturer of this product. For more detailed information on the following specification data please contact head office at VersaFrame Inc. and we will provide further information.

Python Specification Data

Composition and Materials: UV stable, polyester composite.

Maintenance: Properly installed, is maintenance-free

Color: Dark Grey

Installation: Easily installed without special tools. Joins can be simply cut square, butted and caulked without connectors or fables. Won't dent, crack, or rust, and has no sharp edges.

Is flexible, easy-to-handle and transport, and conforms to any roof pitch from 2/12 to 20/12.

Net Free Area: Is 18 sq. in. per lin. ft. Must be installed with soffit vents to meet HVI recommendations.

Air flow is unrestricted by any fabric covering.

Air Permeability.....	ASTM D737	760 cu. ft. per minute
Tear and Tensile Strength.....	ASTM D1294-86.....	Tear: Machine 25 p.p.i. Counter 25 p.p.i.
	ASTM D2261-83.....	Tensile: Machine 25 p.p.i. Counter 25 p.p.i.
Self-Ignition Temperature.....	ASTM D1929.....	517° C
Cold Crack Resistance.....	GLIT C115.....	-31° C
Snow Infiltration.....	CRL 5704.....	-0-

