

Butyl Tape Specification Data

The following specification data are as per the manufacturer of this product and are for use as a general guideline only. VersaFrame Inc is solely a supplier/distributor of these products. The following data has not been tested by VersaFrame Inc. but rather supplied by the manufacturer of this product. For more detailed information on the following specification data please contact head office at VersaFrame Inc. and we will provide further information.

Butyl Tape Specification Data

Chemical Product and Company Identification

Product Name:......Mastix[™] Butyl Tape Chemical Name:.....Isobutylene Chemical Family:.....Butyl Mixture

Health Hazard:0-Minimal Flammability Hazard:0-Minimal Reactivity Hazard:0-Minimal

Fire Hazards

Flash Point:>204°C

Method:.....Pensky Marten closed cup

Extinguishing Media:.....Dry chemical, Carbon dioxide, Foam, Water

Special Fire-Fighting

Procedures:.....Large quantities of water will extinguish.

Do not enter confined space without proper protective equipment.

Hazardous Combustion

Products:.....Carbon monoxide. Carbon dioxide.

Physical and Chemical Properties

Volatile (WL)%:......0
Solubility in Water:......Insoluble
Specific Gravity (H20=1):.....1.59-1.64
Evaporation Rate:.....Not applicable
Appearance:....Soft, pliable gum

Color:......Q-126 Off-white to gray

Q-126BB Black Q-126-10 Off-white to gray

Odor:.....None

